

# Polaroid



## P422T Desktop Label Printer

The Polaroid P422T is a durable 4" wide entry-level desktop printer that is both versatile and easy-to-use.

Designed and built to deliver high quality performance at a competitive price point, the affordable printer will print high quality labels all day long, producing thousands of clear, crisp barcode and identification labels per day.

The P422T offers a low initial price, uses the most cost effective supplies available, and is built to last.



### Innovative & Flexible

The printer will take both 1/2" core 72 meter to 110 meter, or 1" core 300-meter thermal transfer ribbons, allowing customer to use whichever supply of ribbons they have available.

### Tough & Durable

The P422T's modular thermal transfer print mechanism is protected by an outer ABS shell which is designed to withstand tough environments.

### Wide Variety of Labels

An ideal choice for:

- Barcode Labels
- Item Labels
- Instruction Labels
- Patient Identification
- Price Tags
- Shipping Labels
- Pharmacy

# Polaroid



Authorized Licensee

# Polaroid



## P422T Specifications

<b>Resolution</b>	8 dots/mm (203 DPI)
<b>Max. print speed</b>	152.4 mm (6")/second
<b>Max. print width</b>	108 mm (4.25")
<b>Max. print length</b>	25,400 mm (1000")
<b>Printing method</b>	Thermal Transfer & Direct Thermal
<b>LCD/LED</b>	1 LED (3 colors: green, amber & red)
<b>SDRAM</b>	64 MB
<b>Flash</b>	128 MB
<b>Ribbon capacity</b>	300 m long, max. OD 67 mm, 1" core (ink coated outside) 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
<b>Ribbon width</b>	40 mm ~ 110 mm (1.6" ~ 4.3")
<b>Media type</b>	Continuous, die-cut, black mark, fan-fold, notched (outside wound)
<b>Media width</b>	20 ~ 112 mm (0.8" ~ 4.4")
<b>Media thickness</b>	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
<b>Media core diameter</b>	25.4 ~ 38 mm (1" ~ 1.5")
<b>Media length</b>	5 ~ 25,400 mm (0.2" ~ 1000")
<b>Media roll capacity</b>	127 mm (5") OD
<b>Standard Interface</b>	USB 2.0, Ethernet, 10/100 Mbps, RS-232 & USB Host
<b>Software support</b>	SAP, Oracle, Windows, Microsoft SQL Server, BarTender, Nice Label
<b>User Options</b>	<ul style="list-style-type: none"><li>• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core</li><li>• External Bluetooth module (serial interface)</li><li>• KP-200 Plus keyboard display unit</li><li>• KU-007 Plus programmable smart keyboard</li></ul>
<b>Dimension</b>	204 mm (W) x 164 mm (H) x 280 mm (D) / 8.03" (W) x 6.46" (H) x 11.02" (D)
<b>Weight</b>	2.5 kg (5.51 lbs)
<b>Safety Regulation</b>	FCC Class B, CE Class B, C-Tick Class B, UL, cUL, TÜV/safety, CCC, EAC, CoC, BIS, KC, Energy Star®
<b>Warranty</b>	2 Years (Bring in) **Warranty period may vary by territory. Please check with your point of purchase.

# Polaroid



## Authorized Licensee

Singapore (HQ)  
All ID Asia Pte Ltd  
+65-6778-0075  
enquiry@allid.com.sg  
www.allid.com.sg

Malaysia  
All ID Asia Sdn Bhd  
+603-8075-1888  
enquiry@allid.com.my  
www.allid.com.my

Indonesia  
PT All ID Indonesia  
+62 21-4517-330  
enquiry@allid.co.id  
www.allid.co.id

Myanmar  
All ID Myanmar  
+959-777499949  
enquiry@allid.com.mm  
www.allid.com.mm

Philippines  
All ID Philippines Inc.  
+632 224 2042  
enquiry@allid.com.ph  
www.allid.com.ph

Asia-Pacific Sales Representations: Bangladesh, Brunei, Cambodia, China, Hong Kong, India, Indonesia, Laos, Macau, Malaysia, Myanmar, Philippines, Singapore, Sri Lanka, Thailand, Vietnam

Product features, specifications and appearances are subject to change without notice. This product is manufactured, distributed, and sold by All ID Asia. ©2020 All Rights Reserved. Polaroid, Polaroid Color Spectrum, and Polaroid Classic Border Logo are trademarks of PLR IP Holdings, LLC used under license. All other trademarks are the property of the respective owner, who has not sponsored, endorsed or approved this product. PLR IP Holdings, LLC does not manufacture this product or provide any Manufacturer's Warranty or support.